

NATIONAL DECLARATION OF PERFORMANCE
no 03C/1111/24

1. **Name and trade name of the construction product:**
Wall Mounted Thermostatic Shower Column
2. **Designation of the construction product type:**
See Annex
3. **Intended use or uses:**
Installation in water supply systems in rooms used for hygienic purposes (in kitchens, toilets, bathrooms, cloakrooms, etc.), in residential and public buildings, in educational rooms, health care, food industry, industrial and service plants
4. **Name and address of the manufacturer's registered office and place of production of the product:**
VADO a division of Norcros group (holdings) limited
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU
Great Britain
Place of production: PRC
5. **Name and address of the authorized representative, if appointed:** -
6. **The national system used to assess and verify the constancy of performance:** 4
7. **National technical specification:**
7a. **Polish Product Standard:**
PN-EN 1111:2017-09 – Sanitary tapware. Thermostatic mixing Columns (PN 10). General technical specification
PN-EN 1112:2008 – Sanitary tapware. Shower outlets for sanitary tapware for water supply systems type 1 and type 2. General technical specification
PN-EN 1113:2015-06 – Sanitary tapware. Shower hoses for sanitary tapware for water supply systems of type 1 and type 2. General technical specification

Name of the accredited certification body, accreditation number and national certificate number or name of accredited laboratory/laboratories and accreditation number: -

7b. **National Technical Assessment:**
Technical Assessment Body/National Technical Assessment Body:
Name of the accredited certification body, accreditation number and certificate number:
8. **Declared performance characteristics:**
- | The essential characteristics of the construction product for the intended use or uses | Declared performance characteristics | Remarks |
|--|--------------------------------------|---------|
| Maximum hot water temperature | ≤ 85°C | |
| Maximum static pressure | ≤ 0.5 MPa (5 bar) | |
| Flow class | S q ≤ 0,33 l/s (20 l/min) | |
9. **Declared performance characteristics:**
The performance of the product specified above is in accordance with all the declared performances listed in point 8.
This national declaration of performance is issued in accordance with the Act of 16 April 2004 on construction products, under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom Ross - Technical Coordinator

Reference number	Product description
CAM-149T-RRK-CP	Wall Mounted Thermostatic Exposed Shower Column - chrome
CAM-149T-RRK-MB	Wall Mounted Thermostatic Exposed Shower Column - matt black
CAM-149T-RRK-MW	Wall Mounted Thermostatic Exposed Shower Column - matt white
CAM-149T-RRK-SBR	Wall Mounted Thermostatic Exposed Shower Column - satin brass

Translation only